

ELECTRICAL PRODUCTS CATALOG



Liquid Tight Flexible Conduit

Flexible Metalico Conduit Pesado Forrado En PVC

Material: Galvanized Steel Strip, Heavy Duty PVC Jacket

Colour: Black / Grey



CAT#	Trade Size	Inside Dia.(mm)		Outside Dia.(mm)		Bending Radius(mm)
		Min	Max	Min	Max	Min
LFC038	3/8"	12.30	12.80	17.50	18.00	55
LFC050	1/2"	15.80	16.30	20.80	21.30	85
LFC075	3/4"	20.70	21.20	26.30	26.70	105
LFC100	1"	26.00	26.60	32.70	33.40	165
LFC125	1-1/4"	34.70	35.40	41.40	42.20	200
LFC150	1-1/2"	40.00	40.60	47.40	48.30	220
LFC200	2"	51.30	51.90	59.40	60.30	280
LFC250	2-1/2"	63.00	63.60	72.10	73.00	370
LFC300	3"	78.00	78.70	87.90	88.90	450
LFC400	4"	101.60	102.60	113.20	114.30	600

Liquid Tight Connector Straight

Conector Recto

Material: Zinc
Standard: UL 514B



CAT#	Trade Size
47038	3/8"
47050	1/2"
47075	3/4"
47100	1"
47125	1-1/4"
47150	1-1/2"
47200	2"
47250	2-1/2"
47300	3"
47400	4"

Liquid Tight Connector 90°

Conector Curvo

Material: Zinc
Standard: UL 514B



CAT#	Trade Size
49038	3/8"
49050	1/2"
49075	3/4"
49100	1"
49125	1-1/4"
49150	1-1/2"
49200	2"
49250	2-1/2"
49300	3"
49400	4"

Liquid Tight Connector Straight

Conector Recto

Material: Malleable Iron



CAT#	Trade Size
47M038	3/8"
47M050	1/2"
47M075	3/4"
47M100	1"
47M125	1-1/4"
47M150	1-1/2"
47M200	2"

Grounding Liquid Tight Connector Straight

Conector Recto Con Aislacion A Tierra

Material: Malleable Iron



CAT#	Trade Size
47MG038	3/8"
47MG050	1/2"
47MG075	3/4"
47MG100	1"
47MG125	1-1/4"
47MG150	1-1/2"
47MG200	2"

Liquid Tight Connector 45°

Conector Curvo 45°

Material: Malleable Iron



CAT#	Trade Size
48M038	3/8"
48M050	1/2"
48M075	3/4"
48M100	1"
48M125	1-1/4"
48M150	1-1/2"
48M200	2"

Grounding Liquid Tight Connector 45°

Conector Curvo 45° Con Aislacion A Tierra

Material: Malleable Iron



CAT#	Trade Size
48MG038	3/8"
48MG050	1/2"
48MG075	3/4"
48MG100	1"
48MG125	1-1/4"
48MG150	1-1/2"
48MG200	2"

Liquid Tight Connector 90°

Conector Curvo 90°

Material: Malleable Iron



CAT#	Trade Size
49M038	3/8"
49M050	1/2"
49M075	3/4"
49M100	1"
49M125	1-1/4"
49M150	1-1/2"
49M200	2"

Grounding Liquid Tight Connector 90°

Conector Curvo 90° Con Aislacion A Tierra

Material: Malleable Iron



CAT#	Trade Size
49MG038	3/8"
49MG050	1/2"
49MG075	3/4"
49MG100	1"
49MG125	1-1/4"
49MG150	1-1/2"
49MG200	2"

PVC Coated Steel Flexible Conduit

Flexible Metalico Conduit Cubierta PVC

Material: Galvanized Steel Strip, Vacuum PVC Jacket

Colour: Black / Grey



Flexible Conduit Coupling 2 Way

Uniones Para Flexible Metalico Con PVC

Material / Finish: Zinc / Electro-Plated
Hexagonal Type, Bright



CAT#	Trade Size
44050	1/2"
44075	3/4"
44100	1"
44125	1-1/4"
44150	1-1/2"
44200	2"

CAT#	Trade Size	Inside Dia.(mm)		Outside Dia. (mm)		Bending Radius(mm)
		Min	Max	Min	Max	Min
PFC038	3/8"	12.30	12.8	17.00	17.50	35
PFC050	1/2"	15.80	16.30	20.20	20.70	65
PFC075	3/4"	20.70	21.20	25.50	26.10	75
PFC100	1"	26.00	26.60	31.60	32.20	100
PFC125	1-1/4"	34.70	35.40	40.80	41.50	125
PFC150	1-1/2"	40.00	40.60	46.60	47.20	150
PFC200	2"	51.30	51.90	58.10	58.70	175
PFC250	2-1/2"	63.00	63.60	71.80	72.40	200
PFC300	3"	78.00	78.70	87.20	87.90	225
PFC400	4"	101.60	102.60	111.20	112.30	275

Flexible Conduit Connector 90°

Conector Curvo 90° Para Flexible Metalico Con PVC

Material: Zinc

Flex to Box

Plum Type, Matte



CAT#	Trade Size
40P038	3/8"
40P050	1/2"
40P075	3/4"
40P100	1"
40P125	1-1/4"
40P150	1-1/2"
40P200	2"
40P250	2-1/2"
40P300	3"
40P400	4"

Flexible Conduit Connector 90°

Conector Curvo 90° Para Flexible Metalico Con PVC

Material / Finish: Zinc / Electro-Plated

Flex to Box

Hexagonal Type, Bright



CAT#	Trade Size
40H038	3/8"
40H050	1/2"
40H075	3/4"
40H100	1"
40H125	1-1/4"
40H150	1-1/2"
40H200	2"
40H250	2-1/2"
40H300	3"
40H400	4"

Flexible Conduit Straight Connector

Conector Recto Para Flexible Metalico Con PVC

Material: Zinc
Flex to Box
Plum Type, Matte



CAT#	Trade Size
41P038	3/8"
41P050	1/2"
41P075	3/4"
41P100	1"
41P125	1-1/4"
41P150	1-1/2"
41P200	2"
41P250	2-1/2"
41P300	3"
41P400	4"

Flexible Conduit Straight Connector

Conector Recto Para Flexible Metalico Con PVC

Material / Finish: Zinc / Electro-Plated
Flex to Box
Hexagonal Type, Bright



CAT#	Trade Size
41H038	3/8"
41H050	1/2"
41H075	3/4"
41H100	1"
41H125	1-1/4"
41H150	1-1/2"
41H200	2"
41H250	2-1/2"
41H300	3"
41H400	4"

Flexible Conduit Coupling

Copla Recto Con Tornillo Para Conducto Flexible

Material: Zinc
EMT to Flex
Plum Type, Matte



CAT#	Trade Size
42P038	3/8"
42P050	1/2"
42P075	3/4"
42P100	1"
42P125	1-1/4"
42P150	1-1/2"
42P200	2"
42P250	2-1/2"
42P300	3"
42P400	4"

Flexible Conduit Coupling

Copla Recto Con Roscado Para Conducto Flexible

Material: Zinc
Rigid to Flex
Plum Type, Matte



CAT#	Trade Size
43P038	3/8"
43P050	1/2"
43P075	3/4"
43P100	1"
43P125	1-1/4"
43P150	1-1/2"
43P200	2"
43P250	2-1/2"
43P300	3"
43P400	4"

Flexible Conduit Coupling

Copla Recto Con Tornillo Para Conducto Flexible

Material / Finish: Zinc / Electro-Plated
Flex to Box
Hexagonal Type, Bright



CAT#	Trade Size
42H038	3/8"
42H050	1/2"
42H075	3/4"
42H100	1"
42H125	1-1/4"
42H150	1-1/2"
42H200	2"
42H250	2-1/2"
42H300	3"
42H400	4"

Flexible Conduit Coupling

Copla Recto Con Roscado Para Conducto Flexible

Material / Finish: Zinc / Electro-Plated
Rigid to Box
Hexagonal Type, Bright



CAT#	Trade Size
43H038	3/8"
43H050	1/2"
43H075	3/4"
43H100	1"
43H125	1-1/4"
43H150	1-1/2"
43H200	2"
43H250	2-1/2"
43H300	3"
43H400	4"

Galvanized Steel Flexible Conduit American Type

Flexible Metalico Conduit Tipo Americano

Material: Galvanized Steel Strip

Colour: Natural Operating



CAT#	Trade Size	Inside Dia.(mm)		Outside Dia.(mm)		Bending Radius(mm)
		Min	Max	Min	Max	Min
GFA038	3/8"	9.52	9.96	14.22	15.49	50
GFA050	1/2"	15.88	16.38	21.84	23.37	75
GFA075	3/4"	20.62	21.21	26.54	28.07	100
GFA100	1"	25.4	26.42	33.02	35.05	125
GFA125	1-1/4"	31.75	33.02	39.37	41.40	160
GFA150	1-1/2"	38.10	40.01	46.99	49.53	190
GFA200	2"	50.80	52.83	59.69	62.23	255

Galvanized Steel Flexible Conduit

Flexible Conduit De Acero Glvanizedo

Material: Galvanized Steel Strip

Colour: Natural Operating



CAT#	Trade Size	Inside Dia.(mm)		Outside Dia.(mm)		Bending Radius(mm)
		Min	Max	Min	Max	Min
GFC038	3/8"	12.30	12.8	15.7	16.20	50
GFC050	1/2"	15.80	16.30	19.20	19.70	65
GFC075	3/4"	20.70	21.20	24.50	25.10	75
GFC100	1"	26.00	26.60	30.40	31.00	100
GFC125	1-1/4"	34.70	35.40	39.60	40.30	125
GFC150	1-1/2"	40.00	40.60	45.20	45.80	150
GFC200	2"	51.30	51.90	56.50	57.10	175
GFC250	2-1/2"	63.00	63.60	70.20	70.80	200
GFC300	3"	78.00	78.70	85.20	85.90	225
GFC400	4"	101.60	102.60	108.50	109.50	275

BX-Flex Squeeze Connector Straight

Conector Recto De Apriete

Material: Zinc

Standard: UL 514B



CAT#	Trade Size
S1038	3/8"
S1050	1/2"
S1075	3/4"
S1100	1"
S1125	1-1/4"
S1150	1-1/2"
S1200	2"
S1250	2-1/2"
S1300	3"
S1400	4"

BX-Flex Squeeze Connector 90°

Conector Curvos De Apriete

Material: Zinc

Standard: UL 514B



CAT#	Trade Size
A1038	3/8"
A1050	1/2"
A1075	3/4"
A1100	1"
A1125	1-1/4"
A1150	1-1/2"
A1200	2"
A1250	2-1/2"
A1300	3"
A1400	4"

Clamp Connector

For NM & SE Cable
Standard: UL 514B

CAT#	Trade Size
RC050	1/2"
RC075	3/4"
RC100	1"



EMT to Flex Coupling

Copla EMT A Flexible
Material: Zinc

CAT#	Trade Size
EF050	1/2"
EF075	3/4"
EF050	1"



Interior Flex Connector

Conector Flexible A Caja
Material: Zinc or Aluminum

CAT#	Trade Size
IFC038	3/8"
IFC050	1/2"
IFC075	3/4"
IFC100	1"



Duplex Connector & BX-Flex, NM & MC Cable Connector

Material: Zinc



HU1001



HU1002



HU1003



HU1004



HU1005

CAT#	Trade Size	K.O. Size
HU1001	3/8"	1/2"
HU1002	3/8"	1/2"
HU1003	3/8"	1/2"
HU1004	3/8"	1/2"
HU1005	3/8"	1/2"

Liquid Tight Flexible Non-Metallic Conduit

Conducto Flexible De PVC No-Metalico

Material: Thermoplastic Polyvinyl Chloride (PVC)

Colour: Grey



CAT#	Trade Size Inch	Inside Dia.(mm)		Outside Dia.(mm)		Bending Radius (mm)
		Min	Max	Min	Max	
LFCP038	3/8"	12.29	12.80	17.53	18.03	51
LFCP050	1/2"	15.80	16.30	20.83	21.34	72.5
LFCP075	3/4"	20.83	21.34	26.16	26.67	108
LFCP100	1"	26.44	27.08	32.77	33.40	165

PVC Flexible Corrugated Conduit

Conducto Corrugado Flexible De PVC No-Metalico

Material: Thermoplastic Polyvinyl Chloride (PVC)

Colour: Black



CAT#	Trade Size Inch	Inside Dia.(mm)		Outside Dia.(mm)		Bending Radius (mm)
		Min	Max	Min	Max	
LFCC038	3/8"	12.29	12.80	17.53	18.03	51
LFCC050	1/2"	15.80	16.30	20.83	21.34	72.5
LFCC075	3/4"	20.83	21.34	26.16	26.67	108
LFCC100	1"	26.44	27.08	32.77	33.40	165

LT Flexible Conduit Straight Connector Non-Metallic

Conector Recto No-Metallico

Material: PVC

Colour: Grey



CAT#	Trade Size
46P038	3/8"
46P050	1/2"
46P075	3/4"
46P100	1"
46P125	1-1/4"
46P150	1-1/2"
46P200	2"

LT Flexible Conduit 90° Connector Non-Metallic

Conector Curvo No-Metallico

Material: PVC

Colour: Grey



CAT#	Trade Size
48P038	3/8"
48P050	1/2"
48P075	3/4"
48P100	1"
48P125	1-1/4"
48P150	1-1/2"
48P200	2"

LT Flexible Conduit Straight Connector Quick Type Non-Metallic

Conector Recto No-Metallico

Material: PVC

Colour: Grey



CAT#	Trade Size
47P038	3/8"
47P050	1/2"
47P075	3/4"
47P100	1"
47P125	1-1/4"
47P150	1-1/2"
47P200	2"

LT Flexible Conduit 90° Connector Quick Type Non-Metallic

Conector Curvo No-Metallico

Material: PVC

Colour: Grey



CAT#	Trade Size
49P038	3/8"
49P050	1/2"
49P075	3/4"
49P100	1"
49P125	1-1/4"
49P150	1-1/2"
49P200	2"

Authorized distributor



汉纳森电气
HANYSEN
PERFECT ELECTRICAL SOLUTION

Tel/Fax:+86 571 82675286

Cell/Wechat:+86 18058129110

Rm1405, Office Building B, Henglong Square,
Xiaoshan District, Hangzhou, Zhejiang, China

info@hanysen.net benson@hanysen.net