

ELECTRICAL PRODUCTS CATALOG



G.I. Conduit



BS4568: PT1 :1970 (Class 4), IEC 61386-1:2008

CAT#	Trade Size	Outside Dia.		Wall Thickness	Length
		Min	Max		
BSP4204	20mm	19.7mm	20mm	1.6±0.15mm	3.75Meters
BSP4254	25mm	24.6mm	25mm	1.6±0.15mm	3.75Meters
BSP4324	32mm	31.6mm	32mm	1.6±0.15mm	3.75Meters
BSP4404	40mm	39.6mm	40mm	1.6±0.15mm	3.75Meters
BSP4504	50mm	49.6mm	50mm	1.8±0.15mm	3.75Meters



BS4568: PT1 :1970 (Class 3), IEC 61386-1:2008

CAT#	Trade Size	Outside Dia.		Wall Thickness	Length
		Min	Max		
BSP4203	20mm	19.6mm	19.9mm	1.4±0.15mm	3.75Meters
BSP4253	25mm	24.4mm	24.9mm	1.4±0.15mm	3.75Meters
BSP4323	32mm	31.5mm	31.8mm	1.4±0.15mm	3.75Meters
BSP4403	40mm	39.4mm	39.7mm	1.4±0.15mm	3.75Meters
BSP4503	50mm	49.4mm	49.7mm	1.6±0.15mm	3.75Meters



BS31: 1940 (Class 3), IEC 61386-1:2008

CAT#	Trade Size	Outside Dia.		Wall Thickness	Length
		Min	Max		
BSP3075	3/4"	18.8mm	19.1mm	1.6±0.1mm	3.75Meters
BSP3100	1"	25.1mm	25.4mm	1.6±0.1mm	3.75Meters
BSP3125	1-1/4"	31.5mm	31.8mm	1.6±0.1mm	3.75Meters

Male Bend 90°



CAT#	Trade Size
OTE20	20mm
OTE25	25mm
OTE32	32mm
OTE38	40mm
OTE50	50mm

Terminal Box 1 Way



CAT#	Size
BSB120	20mm
BSB125	25mm
BSB132	32mm

Through Box 2 Ways



CAT#	Size
BSBT20	20mm
BSBT25	25mm
BSBT32	32mm

Angle Box 2 Ways



CAT#	Size
BSBA20	20mm
BSBA25	25mm
BSBA32	32mm

Tee Box 3 Ways



CAT#	Size
BSB320	20mm
BSB325	25mm
BSB332	32mm

Cross Box 4 Ways



CAT#	Size
BSB420	20mm
BSB425	25mm
BSB432	32mm

Branch-Y Box 3 Ways



CAT#	Size
BSBY20	20mm
BSBY25	25mm
BSBY32	32mm

Twin Through-H Box 4 Ways



CAT#	Size
BSBH20	20mm
BSBH25	25mm
BSBH32	32mm

Branch-U Box 2 Ways



CAT#	Size
BSBU20	20mm
BSBU25	25mm
BSBU32	32mm

Circular Extension Ring



CAT#	Height
BSER16	16mm
BSER20	20mm
BSER25	25mm

Back Outlet Circular Box



CAT#	Size
BOB120	20mm Terminal
BOB125	25mm Terminal
BOBT20	20mm Through
BOBT25	25mm Through
BOBA20	20mm Angle
BOBA25	25mm Angle
BOB320	20mm Tee
BOB325	25mm Tee
BOB420	20mm Cross
BOB425	25mm Cross

20mm Outlet Deeper Box




CAT#	Type
BSBD1	Terminal
BSBDT	Through
BSBDA	Angle
BSBD3	Tee
BSBD4	Cross

Tangent Angle Box 2 Ways



CAT#	Size
BSBL20	20mm
BSBL25	25mm

Looping Box



CAT#	Holes
LBSB1	1x20mm
LBSB2	2x20mm
LBSB3	3x20mm
LBSB4	4x20mm

Solid Elbow



CAT#	Size
BSSE20	20mm
BSSE25	25mm
BSSE32	32mm

Inspection Elbow




CAT#	Size
BSIE20	20mm
BSIE25	25mm
BSIE32	32mm

Inspection Bend



CAT#	Size
BSIB20	20mm
BSIB25	25mm
BSIB32	32mm

Inspection Tee



CAT#	Size
BSIT20	20mm
BSIT25	25mm
BSIT32	32mm

Distance Saddle



CAT#	Size
BSSD20	20mm
BSSD25	25mm
BSSD32	32mm

Brass Male Bush



CAT#	Size
BMB20	20mm
BMB25	25mm
BMB32	32mm

Circular Box Cover



CAT#	Thickness
BSBC	1.0mm

Hook Cover



CAT#	Size
BSHK	20&25mm

Dome Lid



CAT#	Size
BSDL20	20mm
BSDL25	25mm

Hexagonal Locknut



CAT#	Size
BSL20	20mm
BSL25	25mm
BSL32	32mm
BSL40	40mm
BSL50	50mm

Spacer Bar Saddle



CAT#	Size
BSS20	20mm
BSS25	25mm
BSS32	32mm
BSS40	40mm
BSS50	50mm

BS Conduit Coupling



CAT#	Size
BSC20	20mm
BSC25	25mm
BSC32	32mm
BSC40	40mm
BSC50	50mm

Reducer



CAT#	Size
BSR2025	20x25mm
BSR2532	25x32mm
BSR2032	20x32mm

Stopping Plug



CAT#	Size
BSSP20	20mm
BSSP25	25mm
BSSP32	32mm

GI Box

Material: Pre-Galvanized Steel
With Brass Lug & Adjustable Ear
Knockouts: 20mm & 25mm



CAT#	Size mm	Depth mm	Thickness mm
GB335*	3"x3"	35	0.6~1.5
GB347*	3"x3"	47	0.6~1.5
GB635*	3"x6"	35	0.6~1.5
GB647*	3"x6"	47	0.6~1.5

Replace * with required thickness.
06 for 0.6mm, 10 for 1.0mm till 15 for 1.5mm.

Metal Clad Box

Material: Steel with Powder Coated
With Brass Lug & Fixed Ear
Knockouts: 20mm & 25mm



CAT#	Size mm	Depth mm	Thickness mm
GB335*	3"x3"	40	0.6~1.5
GB347*	3"x3"	50	0.6~1.5
GB635*	3"x6"	40	0.6~1.5
GB647*	3"x6"	50	0.6~1.5

Replace * with required thickness.
08 for 0.8mm, 10 for 1.0mm till 15 for 1.5mm.

Adaptable GI Box with Cover

Material: Pre-Galvanized Steel
Knockouts: 20mm & 25mm

CAT#	Size mm	Depth mm	Thickness mm
AGB32*	75*75	50	0.8~1.5
AGB33*	75*75	75	0.8~1.5
AGB42*	100*100	50	0.8~1.5
AGB43*	100*100	75	0.8~1.5
AGB44*	100*100	100	0.8~1.5
AGB62*	150*150	50	0.8~1.5
AGB63*	150*150	75	0.8~1.5
AGB64*	150*150	100	0.8~1.5
AGB66*	150*150	150	0.8~1.5

Replace * with required thickness.
08 for 0.8mm, 10 for 1.0mm till 15 for 1.5mm.



Authorized distributor



汉纳森电气
HANYSEN
PERFECT ELECTRICAL SOLUTION

Tel/Fax:+86 571 82675286
Cell/Wechat:+86 18058129110
Rm1405, Office Building B, Henglong Square,
Xiaoshan District, Hangzhou, Zhejiang, China
info@hanysen.net benson@hanysen.net