

ELECTRICAL PRODUCTS CATALOG



Meter Socket

Features

- Standard meter sockets are manufactured from 1.2-1.5mm galvanized steel sheet with a baked gray powder polyester paint finish to improve corrosion resistance.
- The meter socket is suitable for service voltage 600V AC max.
- Ample gutter space for easy wiring.
- Convenient knockouts in the side back and bottom.
- Lay in type terminals with pressure plates for easy connections.
- The meter socket is designed to fit conduit hubs from 1" up to 2-1/2".



CAT#	Description	Height (mm)	Width(mm)	Depth(mm)
MS100S-4J	1 Phase,100A,4 Jaw, Ring Type	223	190	86
MS100S-4J-H	1 Phase,100A,4 Jaw, Ring Type with Hub			
MS125-4J-R	1 Phase,125A,4 Jaw, Ring Type	291	203	84
MS125-5J-R	1 Phase,125A,5 Jaw, Ring Type			
MS125-4J-RL	1 Phase,125A,4 Jaw, Ringless Type			
MS125-5J-RL	1 Phase,125A,5 Jaw, Ringless Type			
MS200-4J-R	1 Phase,200A,4 Jaw, Ring Type	396	203	108
MS200-5J-R	1 Phase,200A,5 Jaw, Ring Type			
MS200-7J-R	3 Phase,200A,7 Jaw, Ring Type			
MS200-4J-RL	1 Phase,200A,4 Jaw, Ringless Type			
MS200-5J-RL	1 Phase,200A,5 Jaw, Ringless Type			
MS200-7J-RL	3 Phase,200A,7 Jaw, Ringless Type			
MS20-6J-RL	1 Phase,20A,6 Jaw, Ringless Type	355	203	84
MS20-13J-RL	3 Phase,20A,13 Jaw, Ringless Type			
MS320-4J-RL	1 Phase,320A,4 Jaw, Ringless Type	716	332	132

Authorized distributor



汉纳森电气
HANYSEN
PERFECT ELECTRICAL SOLUTION

Tel/Fax:+86 571 82675286

Cell/Wechat:+86 18058129110

Rm1405, Office Building B, Henglong Square,
Xiaoshan District, Hangzhou, Zhejiang, China

info@hanysen.net benson@hanysen.net